



Spur Gear 0.4 MOD 20' PA

Dimensions in mm

No. of Teeth	O.D	P.C.D	Bore "B"	Boss "C"	Width "D"	Length " E"	Materials available				Order Code
							Steel	Brass	Delrin	Stn.Steel	
12	5.6	4.8	3	4.5	5	12	*	*	*	*	S0.4 012*
15	6.8	6.0	3	5.5	5	12	*				S0.4 015*
16	7.2	6.4	3	5.5	5	12	*		*		S0.4 016*
20	8.8	8.0	3	6.0	5	12	*	*	*	*	S0.4 020*
24	10.4	9.6	4	8.0	5	12	*	*		*	S0.4 024*
30	12.8	12.0	4	8.0	5	12	*	*	*		S0.4 030*
32	13.6	12.8	4	8.0	5	12	*	*	*	*	S0.4 032*
36	15.2	14.4	4	10.0	5	12	*	*	*	*	S0.4 036*
40	16.8	16.0	4	10.0	5	12	*	*	*		S0.4 040*
48	20.0	19.2	4	10.0	5	12	*	*	*		S0.4 048*
50	20.8	20.0	4	10.0	5	12			*		S0.4 050*
55	22.8	22.0	4	10.0	5	12	*		*		S0.4 055*
60	24.8	24.0	6	15.0	5	12	*	*	*		S0.4 060*
64	26.4	25.6	6	15.0	5	12	*	*			S0.4 064*
72	29.6	28.8	6	15.0	5	12	*	*	*		S0.4 072*
84	34.4	33.6	6	15.0	5	12			*		S0.4 084*
90	36.8	36.0	6	15.0	5	12	*		*	*	S0.4 090*
96	39.2	38.4	6	15.0	5	12			*		S0.4 096*
100	40.8	40.0	6	15.0	5	12		*			S0.4 100*
108	44.0	43.2	6	15.0	5	12			*		S0.4 108*
120	48.8	48.0	6	15.0	5	12	*		*	*	S0.4 120*

Material Specifications

Steel BS970 220M07
Delrin 150

Brass BS2874 CZ 121
Stainless Steel BS970 431 S29 or BS970 441 S49T

If not shown, we can manufacture to your exact requirements