



Spur Gear 0.8 MOD 20'PA

Dimensions in mm

No. of Teeth	O.D	P.C.D	Bore "B"	Boss "C"	Width 'D'	Length " E"	Materials available			Order Code
							Steel	Brass	Delrin	
10	9.6	8.0	4	9.6	6	14	*	*	*	S0.8 010*
15	13.6	12.0	4	13.6	6	14	*	*	*	S0.8 015*
16	14.4	12.8	4	10	6	14	*	*	*	S0.8 016*
20	17.6	16.0	6	12	6	14	*	*	*	S0.8 020*
24	20.8	19.2	6	12	6	14	*	*	*	S0.8 024*
25	21.6	20.0	6	12	6	14	*	*	*	S0.8 025*
30	25.6	24.0	6	12	6	14	*	*	*	S0.8 030*
32	27.2	25.6	6	12	6	14	*	*	*	S0.8 032*
35	29.6	28.0	8	19	6	14	*	*	*	S0.8 035*
40	33.6	32.0	8	19	6	14	*	*	*	S0.8 040*
45	37.6	36.0	8	19	6	14	*	*	*	S0.8 045*
50	41.6	40.0	8	19	6	14	*	*	*	S0.8 050*
55	45.6	44.0	8	19	6	14	*	*	*	S0.8 055*
60	49.6	48.0	10	22	6	14	*	*	*	S0.8 060*
64	52.8	51.2	10	22	6	14	*	*	*	S0.8 064*
65	53.6	52.0	10	22	6	14	*	*	*	S0.8 065*
75	61.6	60.0	10	22	6	14	*	*	*	S0.8 075*
80	65.6	64.0	10	22	6	14	*	*	*	S0.8 080*
90	73.6	72.0	10	22	6	14	*	*	*	S0.8 090*
95	77.6	76.0	10	22	6	14	*	*	*	S0.8 095*
96	78.4	76.8	10	22	6	14	*	*	*	S0.8 096*
100	81.6	80.0	10	26	6	14	*	*	*	S0.8 100*
120	97.6	96.0	10	26	6	14	*	*	*	S0.8 120*

Material Specifications

Steel BS970 220M07.
Delrin 150.

Brass BS2874 CZ 121.

If not shown, we can manufacture to your exact requirements.