



Spur Gear 24DP 20' PA

Dimensions in inches

AVAILABLE IN STEEL ONLY

No. of Teeth	O.D	P.C.D	Bore "B"	Boss "C"	Width 'D'	Length " E"	Order Code
15	0.708	0.625	0.313	0.500	0.312	0.812	S024 015S
20	0.917	0.833	0.313	0.625	0.312	0.812	S024 020S
25	1.125	1.042	0.313	0.812	0.312	0.812	S024 025S
30	1.333	1.250	0.375	1.000	0.312	0.812	S024 030S
35	1.542	1.458	0.375	1.000	0.312	0.812	S024 035S
40	1.750	1.667	0.375	1.000	0.312	0.812	S024 040S
45	1.958	1.875	0.375	1.000	0.312	0.812	S024 045S
50	2.167	2.083	0.375	1.000	0.312	0.812	S024 050S
55	2.375	2.292	0.375	1.000	0.312	0.812	S024 055S
60	2.583	2.500	0.375	1.000	0.312	0.812	S024 060S
63	2.708	2.625	0.375	1.000	0.312	0.812	S024 063S
65	2.792	2.708	0.375	1.000	0.312	0.812	S024 065S
70	3.000	2.917	0.375	1.000	0.312	0.812	S024 070S
80	3.417	3.333	0.375	1.000	0.312	0.812	S024 080S
85	3.625	3.542	0.500	1.250	0.312	0.937	S024 085S
100	4.250	4.167	0.500	1.250	0.312	0.937	S024 100S
120	5.083	5.000	0.500	1.250	0.312	0.937	S024 120S

Material Specification

Steel BS970 220M07

If not shown, we can manufacture to your exact requirements